# SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Chemical Name Mixture CAS No. Mixture

Trade Name CU4 CARPET & UPHOLSTERY CLEANER

Product Code 10-500-10.01,10-500-5%VOC,10-500-HOME,10-500-

6,10-500870,10-500870-1.01

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Carpet cleaning agent

Uses Advised Against None

Company Identification Spray Products Corporation

P.O. Box 737

Norristown, PA 19404

Pizazz Indernational Promotions, Inc

106-950 Alsgard St Kelowna, BC V1X 7J2

Canada

Telephone (610) 277-1010 Fax (610) 277-4390

E-Mail (competent person) <a href="mailto:sds@sprayproducts.com">sds@sprayproducts.com</a>

**Emergency telephone number** 

Emergency Phone No. Transportation Emergency: CHEMTREC 24 hr. 1-800-424-

9300 / 1 (703) 527-3887 (Collect calls accepted)

### **SECTION 2: HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 2; Liquefied gas; Eye Irrit. 2

#### Label elements

Hazard Symbol



Signal word(s)

Hazard Statement(s) Flammable aerosol

Contains gas under pressure; may burst if heated.

Causes serious eye irritation.

Precautionary Statement(s) Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Wear eye/face protection.

Wash hands and exposed skin after use.

Protect from sunlight and do not expose to temperatures exceeding 50

°C/122 °F.

Other hazards None known

Revision: March 22, 2018 Page: 1/6

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Propane	1 5	1 - 5 74-98-6	Flam. Gas 1, H220
Fiopalie	1-3		Liquefied gas; H280
Butane	1 5	- 5 106-97-8	Flam. Gas 1, H220
Dutane	1-5		Liquefied gas; H280
			Acute Tox. 2 (Inhalation);H330
Sodium lauroyl sarcosinate	0.1 – 1	137-16-6	Skin Irrit. 2; H315
			Eye Dam. 1; H318
polyethylene glycol octylphenyl ether	01 05	0.1 – 0.5 9002-93-1	Acute Tox. 4 (oral); H302
polyethylene glycol octylphenyl ethel	0.1 – 0.3		Eye Dam. 1; H318
			Met. Corr. 1; H290
Sodium hydroxide	0.01 - 0.05	1310-73-2	Skin Corr. 1A; H314
			Eye Dam. 1; H318
			Skin Corr. 1B; H314
Silicic acid, disodium salt (1:2)	0.25 - 0.75	6834-92-0	Eye Dam. 1; H318
			STOT SE 3; H335

Additional Information - Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.: None

#### **SECTION 4: FIRST AID MEASURES**



#### Description of first aid measures

Inhalation Move person to fresh air. If breathing is labored, administer oxygen. If

symptoms develop, obtain medical attention.

Skin Contact Wash affected skin with soap and water. If symptoms develop, obtain

medical attention.

Eye Contact Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If symptoms occur

obtain medical attention.

Ingestion Do not give anything by mouth to an unconscious person. Seek medical

treatment.

Most important symptoms and effects, both acute and

None

Indication of any immediate medical attention and

special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

### **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

-Suitable Extinguishing Media

-Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Special hazards arising from the substance or

mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

Revision: March 22, 2018 Page: 2/6

<sup>\*</sup> The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

emergency procedures

Take precautionary measures against static discharges. Avoid contact

with skin and eyes. Avoid breathing vapors.

Environmental precautions Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Transfer to a container for

disposal or recovery.

Reference to other sections None
Additional Information None

## **SECTION 7: HANDLING AND STORAGE**

Precautions for safe handling Keep away from heat/sparks/open flames/hot surfaces. – No

smoking. Avoid contact with skin and eyes. Use product in a well-

ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature Keep in a cool, well ventilated place. Store at temperatures not

exceeding 50 °C / 122 °F.

-Incompatible materials This product should be stored away from sources of strong heat or

oxidizing chemicals.

Specific end use(s) Carpet cleaning agent

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Occupational Exposure Limits**

		(8hr TWA)		(STEL)		
		PEL	TLV	PEL	TLV	
SUBSTANCE.	CAS No.	(OSHA)	(ACGIH)	(OSHA)	(ACGIH)	Note:
n-Butane	106-97-8		250 ppm			
Propane	74-98-6	1000 ppm	Aspyx.#			#

<sup>\*</sup>Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

None - Not normally required.

**Exposure controls** 

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure

limit is not exceeded.

Personal protection equipment

Eye/face protection Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.

Revision: March 22, 2018 Page: 3/6

Thermal hazards Not normally required. Use gloves with insulation for thermal

protection, when needed.

Not available

Not available

Not available

Environmental Exposure Controls None known

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Appearance Liquid
Color. Colorless
Odor Characteristic.
Odor Threshold (ppm) Not available
pH (Value) Not available
Melting Point (°C) / Freezing Point (°C) Not available

Boiling point/boiling range (°C):

Flash Point (°C)

Evaporation Rate

Flammability (solid, gas)

Not available

Flammable

Explosive Limit Ranges

2.1% - 9.5% v/v (Propane)

Vapor pressure (Pascal)

Vapor Density (Air=1)

Density (g/ml)

2.1% - 9.5% v/v (Propane)

ca. 95 x 10<sup>4</sup> (Propane)

ca. 1.56 @ 0 °C (Propane)

Not available

Density (g/ml)
Solubility (Water)
Solubility (Other)
Partition Coefficient (n-Octanol/water)

Auto Ignition Point (°C) 450 (Propane)
Decomposition Temperature (°C) Not available
Kinematic Viscosity (cSt) Not available
Explosive properties Not explosive.
Oxidizing properties Not oxidizing.
Other information Not available

#### **SECTION 10: STABILITY AND REACTIVITY**

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoid Avoid contact with heat and ignition sources.

Incompatible materials Strong oxidizing agents

Hazardous decomposition product(s)``` None known

### **SECTION 11: TOXICOLOGICAL INFORMATION**

Exposure routes: Inhalation, Skin Contact, Eye Contact

Acute toxicity LD50 >5000 mg/kg-bw Irritation / Corrosivity Causes serious eye irritation.

# **SECTION 12: ECOLOGICAL INFORMATION**

Aquatic toxicity:

Short term Not available Long Term Not available

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods Disposal should be in accordance with local, state or national

legislation. Consult an accredited waste disposal contractor or the

local authority for advice.

Revision: March 22, 2018 Page: 4/6

#### **SECTION 14: TRANSPORT INFORMATION**

Sea transport Air transport U.S. DOT (IMDG) (ICAO/IATA) **UN** number 1950 1950 1950 **Proper Shipping Name** Aerosols, flammable Aerosols, flammable Aerosols, flammable Transport hazard class(es) 2.1 2.1 21 Packing group Not applicable Not applicable Not applicable **Environmental hazards** None assigned None assigned None assigned Special precautions for user None assigned None assigned None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

#### **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)	
None				

SARA 311/312 - Hazard Categories: See SECTION 2: HAZARDS IDENTIFICATION

#### SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.	
None			

#### SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

#### California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None		

#### **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: 1-16.

Date of preparation: July 5, 2017

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

#### Hazard Statement(s)

- H220: Extremely flammable gas.
- H223: Flammable aerosol.
- H226: Flammable liquid and vapour.
- H280: Contains gas under pressure; may explode if heated.
- H290: May be corrosive to metals.
- H302: Harmful if swallowed.
- H314: Causes severe skin burns and eye damage.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H320: Causes eye irritation.
- H330: Fatal if inhaled.
- H335: May cause respiratory irritation.
- H351: Suspected of causing cancer.

Revision: March 22, 2018 Page: 5/6

#### Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Revision: March 22, 2018 Page: 6/6