

LT5 LEATHER PROTECTOR CONSUMER

SAFETY DATA SHEET

According to Canada's Hazardous Products Regulations (HPR) SOR/2015-17

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	LT5 Leather Protector Consumer
Product Code	None

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Leather Care / Consumer Product
Uses Advised Against	None
Company Identification	Spray Products Corporation P.O. Box 737 Norristown, PA 19404
Telephone	(610) 277-1010
Fax	(610) 277-4390
E-Mail (competent person)	sds@sprayproducts.com

Emergency telephone number

Emergency Phone No.	Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)
---------------------	---

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

HPR/WHIMIS 2015 / GHS Classification	Flam. Aerosol 2; Liquefied gas; Skin Irrit. 2; Asp. Tox. 1; STOT SE 3
--------------------------------------	---

Label elements

Hazard Symbol



DANGER

Signal Word(s)

Hazard Statement(s)

Flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Wash hands and exposed skin after use.
Wear protective gloves/protective clothing/eye protection/face protection.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statement(s)

Other hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

LT5 LEATHER PROTECTOR CONSUMER

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt.	CAS No.	Hazard classification
Distillates (petroleum), hydrotreated light	5 - 15	64742-47-8	Flam. Liq. 4; H227 Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Propane	5 - 6	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
n-Butane	4 - 5	106-97-8	Flam. Gas 1, H220 Press. Gas (*)
Ammonia, aqueous solution	0.8	1336-21-6	Skin Irrit. 2; H315 Eye Irrit. 2; H319
Water	65 - 70	7732-18-5	Not classified as dangerous for supply/use.
Polydimethyl siloxane	1 - 10	63148-62-9	Not classified as dangerous for supply/use.
[2-(2 methoxymethylethoxy)methylethoxy]propanol	3 - 5	25498-49-1	Not classified as dangerous for supply/use.
Sorbitan monooleate	0.1 - 1	1338-43-8	Not classified as dangerous for supply/use.

Additional Information - None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation	Move person to fresh air. If breathing is laboured, administer oxygen. If symptoms develop, obtain medical attention.
Skin Contact	Wash affected skin with soap and water. If symptoms develop, obtain medical attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
Ingestion	Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed Aspiration of droplets may cause pulmonary oedema.

Indication of any immediate medical attention and special treatment needed IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media	Extinguish with carbon dioxide, dry chemical, foam or water spray.
-Unsuitable Extinguishing Media	Do not use water jet.

Special hazards arising from the substance or mixture

Pressurised container: May burst if heated

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing

LT5 LEATHER PROTECTOR CONSUMER

should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Prevent liquid entering sewers, basements and workpits.
Environmental precautions	
Methods and material for containment and cleaning up	Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.
Reference to other sections	None
Additional Information	None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing dust/fume/gas/mist/vapours/spray.
Conditions for safe storage, including any incompatibilities	
-Storage temperature	Store in a well-ventilated place. Protect from sunlight. Store at temperatures not exceeding 50 °C / 122 °F.
-Incompatible materials	This product should be stored away from sources of strong heat or oxidising chemicals.
Specific end use(s)	Leather Care / Consumer Product

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		OEL (Canada)	TLV (ACGIH)	OEL (Canada)	TLV (ACGIH)	
C ₉ -C ₁₅ Alkanes & Cycloalkanes	Mixture	-----	1200 mg/m ³	-----	-----	
n-Butane	106-97-8	800 ppm	250 ppm	-----	-----	-----
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#

#Assure minimum oxygen content of work atmosphere.

Recommended monitoring method NIOSH 1500 (hydrocarbons, B.P. 36 - 216 °C); NIOSH 1550 (Naphthas)

Exposure controls

Appropriate engineering controls Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).



LT5 LEATHER PROTECTOR CONSUMER

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber). Check with protective equipment manufacturer's data.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Aerosol spray
Color.	Clear
Odour	Fuel oil-like.
Odour Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Flammable aerosol
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapour pressure (Pascal)	ca. 95×10^4 (Propane)
Vapour Density (Air=1)	ca. 1.56 @ 0 °C (Propane)
Density (g/ml)	Not available.
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	< 20.5 @ 40 0°C
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Other information	Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	This product should be stored away from sources of strong heat or oxidising chemicals.
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke, Other

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

LT5 LEATHER PROTECTOR CONSUMER

Hydrotreated Light Distillate (CAS No. 64742-47-8) - By analogy with similar materials:

Acute toxicity (calculated / estimated)	Oral: LD50 >5000 mg/kg-bw Dermal: LD50 >2000 mg/kg-bw Inhalation: LC0 ≥5.28 mg/l (Vapour), 4-hr. rat - May cause drowsiness or dizziness.
Irritation/Corrosivity	Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Sensitisation	It is not a skin sensitizer.
Repeated dose toxicity	Oral: NOEL 750 mg/kg Dermal: NOEL 0.5 ml/kg bw Inhalation: NOEL ≥1000 mg/m3
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	Not to be expected
Reproductive toxicity	Not to be expected

Propane (CAS# 74-98-6):

Acute toxicity	Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)
Irritation/Corrosivity	No evidence of irritant effects from normal handling and use.
Sensitisation	It is not a skin sensitizer.
Repeated dose toxicity	NOAEC: ≥19678 mg/m3 (28-day, rat, Systemic effects) LOAEC: 21641 mg/m3 (28-day, rat, effects: Body weight)
Carcinogenicity	No data. It is unlikely to present a carcinogenic hazard to man.
Mutagenicity	There is no evidence of mutagenic potential.
Reproductive toxicity	None anticipated

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Hydrotreated Light Distillate (CAS No. 64742-47-8) - By analogy with similar materials:

Short term	LC50 (96 hour): 2.5 mg/L (fish) EC50 (48 hour): 1.4 mg/L (crustacea) EC50 (72 hour): 1.3 mg/L (algae)
Long Term	NOEC (28 days): 0.098 mg/L (fish) LOEC (21 days): 1.2 mg/L (crustacea) LOEL (72 hour): 1 mg/L (algae)

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
--------------------------------	--

SECTION 14: TRANSPORT INFORMATION

	Land transport (TDG)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned

LT5 LEATHER PROTECTOR CONSUMER

Special precautions for user

None assigned

None assigned

None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

This product has been classified in accordance to CPR Section 12 and the MSDS contains all the information required by the CPR.

Canada (DSL/NDSL) - All chemicals listed.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: July 2, 2016

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H227: Combustible liquid.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness.
- H401: Toxic to aquatic life.
- H411: Toxic to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.