SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name Mixture CAS No. Mixture

Trade Name GP3 GENERAL PURPOSE CLEANER

Product Code 10-545-6

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)

Cleaning product

Uses Advised Against None

Company Identification Spray Products Corporation

P.O. Box 737

Norristown, PA 19404

Telephone (610) 277-1010 Fax (610) 277-4390

E-Mail (competent person) <u>sds@sprayproducts.com</u>

Emergency telephone number

Emergency Phone No. Transportation Emergency: CHEMTREC 24 hr. 1-800-424-

9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Liquefied gas

Label elements

Hazard Symbol



Signal word(s)

Hazard Statement(s)

WARNINGContains gas under pressure; may explode if heated.

Precautionary Statement(s)

Do not pierce or burn, even after use.

Wash hands and exposed skin after use.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/

122°F.

Other hazards None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Propane	1 - 5	74-98-6	Flam. Gas 1, H220
Proparie	1-5	74-90-0	Press. Gas (*)
Butane	1 - 5	106-97-8	Flam. Gas 1, H220
Butane		1-5 100-97-8	Press. Gas (*)
Ethanol	1-2	64-17-5	Flam. Liq. 2; H225
Emanoi		04-17-5	Eye Irrit. 2: H319

Revision: January 3, 2018 Page: 1/6

			Flam. Liq. 2; H225		
Methanol	<1	67-56-1	Acute Tox. 3; H301, H311, H331		
			STOT SE 1; H370 (Optic nerve, Central nervous system)		
			Acute. Tox. 4; H302, H312, H332		
2-Butoxyethanol	1 - 5	111-76-2	Skin Irrit. 2; H315		
			Eye Irrit. 2a; H319		
			Acute Tox. 2 (Inhalation); H330		
Sodium N-lauroylsarcosinate	<0.1	137-16-6	Skin Irrit. 2; H315		
-			Eye Dam. 1; H318		
Polyethylene glycol <0.1 9036-19-5		9036-19-5	Acute Tox. 4 (oral); H302		
octylphenyl ether	~ 0.1	9030-19-3	Eye Dam. 1; H318		
Poly(ethylene oxide)	<0.1	25322-68-3	STOT SE 3: H335		

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation Move person to fresh air. If breathing is laboured, administer oxygen. If

symptoms develop, obtain medical attention.

Skin Contact Wash affected skin with soap and water. If symptoms develop, obtain

medical attention.

Eye Contact Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If irritation develops

and persists, get medical attention.

Ingestion Immediately call a POISON CENTER or doctor/physician. Do not give

anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

None anticipated

Indication of any immediate medical attention and

special treatment needed

None anticipated

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media

-Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Do not use water jet.

Special hazards arising from the substance or

mixture

Pressurised container: May burst if heated

Advice for fire-fighters A self contained breathing apparatus and suitable protective clothing

should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

Revision: January 3, 2018 Page: 2/6

^{*} The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

emergency procedures

Avoid contact with skin and eyes.

Environmental precautions Prevent liquid entering sewers, basements and workpits.

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Transfer to a container for

disposal or recovery.

Reference to other sections None Additional Information None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Do not pierce or burn, even after use. Avoid contact with skin and

eves.

Conditions for safe storage, including any incompatibilities

-Storage temperature Store in a well-ventilated place. Protect from sunlight. Do not expose

to temperatures exceeding 50°C/ 122°F.

-Incompatible materials This product should be stored away from sources of strong heat or

oxidizing chemicals.

Specific end use(s) Cleaning product

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

		(8hr TWA)		(STEL)		
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
n-Butane	106-97-8		250 ppm			
Propane	74-98-6	1000 ppm	Aspyx.#			#
Ethanol	64-17-5	1000 ppm			1000 ppm	
Methanol	67-56-1	200 ppm	200 ppm		250 ppm	Skin
2-Butoxyethanol	111-76-2	50 ppm	20 ppm			

^{*}Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 216 $^{\circ}$ C); NIOSH 1400 (Alcohols I); NIOSH 1403 (Alcohols IV)

Exposure controls

Appropriate engineering controls

Use only with adequate ventilation to keep exposures (airborne levels of dust, fume, vapour etc) below recommended exposure limits.

Personal protection equipment

Eye/face protection Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber).



Revision: January 3, 2018 Page: 3/6

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.



Thermal hazards Not normally required.

Environmental Exposure Controls None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Liquid / Liquefied gas

Color. Clear

Odor Not available
Odor Threshold (ppm) Not available
pH (Value) Not available
Melting Point (°C) / Freezing Point (°C) Not available

Boiling point/boiling range (°C):

Flash Point (°C)

Evaporation Rate

Not available

Not available

Not available

Not available

Flammability (solid, gas)

Non-flammable Aerosol

Explosive Limit Ranges Not available

Vapor pressure (Pascal)

Vapor Density (Air=1)

ca. 95 x 10⁴ (Propane)

ca. 1.56 @ 0°C (Propane)

Density (g/ml)

Solubility (Water)

Solubility (Other)

Not available

Not available

Partition Coefficient (n-Octanol/water)

Auto Ignition Point (°C)

Decomposition Temperature (°C)

Not available

Not available

Kinematic Viscosity (cSt) <20

Explosive properties

Oxidizing properties

Not explosive.

Not oxidizing.

Other information

Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoid Avoid contact with heat and ignition sources.

Incompatible materials Strong oxidizing agents

Hazardous decomposition product(s) None known

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Mixtures

Acute toxicity LD50 >5000 mg/kg-bw Irritation / Corrosivity Causes serious eye irritation.

Substances in preparations / mixtures

Methanol (CAS# 67-56-1)

Revision: January 3, 2018 Page: 4/6

Acute toxicity * LD50 (oral, monkey): 7000 mg/kg-bw

LD0 (oral, rat): ≥ 2528 mg/kg-bw LC50 (inhal., cat, 6-hours): 43.68 mg/L LC50 (inhal., monkey, 4-hours): 52 mg/L Ingestion may damage the optic nerve. May cause dizziness and drowsiness.

IrritationMay cause eye irritation.SensitisationIt is not a skin sensitiser.

 Repeated dose toxicity
 NOAEC (2-yr. inhal., mouse): ≥ 1.3 mg/L

 Developmental Toxicity
 Negative. Not a specific developmental toxin.

 Toxicity for reproduction
 Negative. Not a specific reproductive toxin.

Mutagenicity Negative

Carcinogenicity Probably not carcinogenic to humans.

Other information * ATE (oral) = 100 mg/kg * ATE (dermal) = 300 mg/kg

* ATE (inhalation) = 3 mg/L

Propane (CAS# 74-98-6):

Acute toxicity Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)

Irritation/Corrosivity

No evidence of irritant effects from normal handling and use.

Sensitisation It is not a skin sensitiser.

Repeated dose toxicity NOAEC: ≥19678 mg/m3 (28-day, rat, Systemic effects)

LOAEC: 21641 mg/m3 (28-day, rat, effects: Body weight)

Carcinogenicity

No data. It is unlikely to present a carcinogenic hazard to man.

Mutagenicity There is no evidence of mutagenic potential.

Reproductive toxicity

None anticipated

SECTION 12: ECOLOGICAL INFORMATION

Aquatic toxicity:

 Short term
 LC50 (96 hour): >100 mg/L (Fish)

 Long Term
 NOAEC (28 days): >100 mg/l (Fish) QSAR

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Disposal should be in accordance with local, state or national

legislation. Consult an accredited waste disposal contractor or the

local authority for advice.

SECTION 14: TRANSPORT INFORMATION

Sea transport Air transport U.S. DOT (IMDG) (ICAO/IATA) 1950 **UN** number 1950 1950 **Proper Shipping Name** Aerosols, non-flammable Aerosols, non-flammable Aerosols, non-flammable Transport hazard class(es) 2.2 2.2 2.2 Packing group Not applicable Not applicable Not applicable **Environmental hazards** None assigned None assigned None assigned Special precautions for user None assigned None assigned None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

Revision: January 3, 2018 Page: 5/6

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Methanol	67-56-1	< 1	5000

SARA 311/312 - Hazard Categories: Refer to SECTION 2 - HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Methanol	67-56-1	< 1

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
Methanol	67-56-1	Developmental

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: January 2, 2018

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapour.
- H301: Toxic if swallowed.
- H302: Harmful if swallowed.
- H311: Toxic in contact with skin.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H330: Fatal if inhaled.
- H331: Toxic if inhaled.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.
- H370: Causes damage to organs.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Revision: January 3, 2018 Page: 6/6